



KWS ELECTRONIC
HIGH FREQUENCY TEST EQUIPMENT

THE NEW VAROS 306

- 5" VGA color-TFT
 - Frequency range 5 MHz – 2.150 MHz
 - Level measurement for analog signals (FM/TV/SAT) with audio and video demodulation
 - Level measurement for return path frequencies 5-65 MHz
 - DVB-S, DVB-C and DVB-T: Level, BER, MER
 - MPEG 2 audio and video
 - Analyzer mode for all ranges
 - Video and audio in/out via Scart, DVI out
 - Storage of measurements directly on a USB stick
 - CI-slot for one CA-module with Smartcard
 - Mains operation and 12 V external feed, powerful NiMH batteries
- Options available:**
- DVB-S2-frontend
 - MPEG 2/4 decoder for video and audio demodulation of SD and HD signals



Easy handling:

The large 5" color-TFT is - same as the speaker - built into the instrument's hinged cover.

The rotary pulse encoder, the A/V-adjustment, the keypad and the IEC- input socket are on the front plate.

VAROS KWS STANDARD-SERIE



Safe and easy handling

in situations where working is difficult. The VAROS design with an ideal centre of gravity and also the sturdy protection case will support your work on-site.

Overall view is important:

Measurement data or TV pictures can be shown in the combined display. The enlarged data display enables for precise working even in poor lighting.

KWS-Electronic GmbH

Tattenhausen · Sportplatzstrasse 1
83109 Großkarolinenfeld · Germany

Phone +49.80 67.90 37-0 · Telefax +49.80 67.90 37-99
info@kws-electronic.de · www.kws-electronic.de